Barrier Wall Performance Monitoring

McCormick & Baxter Monthly Progress Meeting

November 18, 2003






Overview

- 45 monitoring wells were installed inside and outside the Barrier Wall.
- Well clusters were installed along the riverfront and Willamette Cove (shallow, intermediate, deep).
- Well clusters screened at the same intervals.







Continued...

- No product or sheen observed in riverfront wells during well development.
 - Heavy sheen was observed in MW-56s during well development;
 - Slight H.C. odor noticed in MW-36s
- 24 pressure transducers installed to collect continuous data across the site and in the Willamette Cove.




Continued...

- Data collected hourly for the first month (frequency will be reduced after one month).
 - Pressure transducers downloaded using a Palm Pilot at each well location.
 - Currently evaluating the use of radio transmitters to send real time data directly to a computer system.



DRAFT
FWDA Shallow Groundwater Elevation
Inside the Barrier Wall vs Outside the Barrier Wall





DRAFT
TFA Shallow Groundwater Elevation
Inside the Barrier Wall vs Outside the Barrier Wall

Date

10/20/2003 11:49

10/21/2003 11:49

10/22/2003 11:49


10/23/2003 11:49

10/25/2003 11:49

10/24/2003 11:49




DRAFT
TFA Intermediate Groundwater Elevation
Inside the Barrier Wall vs the Willamette River





DRAFT
TFA Intermediate Groundwater Elevation
Inside the Barrier Wall vs the Willamette River




.

MW44d

Willamette River

DRAFT
TFA Deep Groundwater Bevation Well
Inside the Barrier Wall vs the Willamette River



MW-45d

Draft
TFA Deep Groundwater Elevation
Outside the Barrier Wall vs the Willamete River

Date

Approximate Elevation (ft-NGVD)


10/20/2003 11:25

10/21/2003 11:25

10/23/2003 11:25

10/22/2003 11:25

10/24/2003 11:25



Preliminary Interpretations

- A strong hydraulic connection exists between s, i, d zones and river stage in wells located outside the barrier wall along the riverfront in the TFA and FWDA.
- Tidal influences on the shallow zone inside the wall are strongly dampened.
- In FWDA, downward vertical gradient on the inside and an upward gradient on the outside.



What's Next

- Complete the installation of the river transducer and radio transmitter.
- Continue to analyze groundwater data and present that data to the group in the Monthly meetings.
- Develop an outline and schedule for reporting.
- Complete evaluation of an automated groundwater collection vs. manual downloading at each well.

